

# FLATWRAP® HP

## Housewrap

Convenient 500 sq ft roll allows for simple one man installation

Meets tear and wind load resistance requirements for jobs over 40 ft.

Taping of seams is not required, reducing both materials and labor costs

Tri-laminate design resists damage from surfactants that can compromise other brands of housewrap

Ideal water resistive barrier to be used in combination with Slicker family of rainscreen products



FlatWrap® HP is a commercial-grade water-resistive barrier with enhanced tear resistance. The product features a high performance tri-laminate design versus typical weather resistant barriers. When used in conjunction with a rainscreen it provides superior bulk water drainage, exceptional vapor permeability, and durability. FlatWrap® HP is the ideal WRB with Slicker Classic and Slicker MAX Rainscreens.



## FLATWRAP® HP

COMMERCIAL-GRADE WRB

<b>WIDTH</b>	5 ft (1.5 m)
<b>LENGTH PER ROLL</b>	100 ft (30.48 m)
<b>MAX. UV EXPOSURE</b>	180 days
<b>WARRANTY</b>	10 (product) or 15 (system) year limited
<b>COMPOSITION</b>	Polypropylene tri-laminate
<b>VAPOR PERMEABILITY</b>	35 perms
<b>FIRE RATING</b>	Class A