



HYDROFLASH™ SELF-ADHERED FLASHING

PHYSICAL PROPERTIES DATA SHEET

Properties	Test Standard	HydroFLASH™ Performance
Nail Sealability	AAMA 711-07	PASS
90° Peel Adhesion - Plywood	AAMA 711-07 Section 5.3	5.4 lb/in
90° Peel Adhesion - OSB		4.6 lb/in
90° Peel Adhesion - Aluminum		6 lb/in
90° Peel Adhesion - Vinyl		5 lb/in
Chemical Compatibility	AAMA 713-08 (Random sampling of sealants)	PASS
Mold Growth	ASTM G-21	No Growth
Shelf Life	N/A	2 years in original packaging

PRODUCT INFORMATION

- Specially formulated for aggressive adhesion to HydroGap™ Drainable Housewrap and FlatWrap HP
- Available in 4 in, 6 in, 9 in, or 12 in
- Length: 75 ft
- Split-release liner
- Seals around fasteners
- Fungicide additive restricts mold growth
- Can be applied to damp surfaces
- Excellent adhesion to unprimed concrete
- Compatible with a wide array of sealants
- No primer needed
- No VOCs, HFCCs, CFCs
- AAMA 711 approved
- Meets criteria of AC 148
- 10 or 15-year limited warranty

INSTALLATION CONSIDERATIONS

Intended for use on these surfaces: Housewrap, Felt/Building Paper, Plywood, OSB, Rigid Foam Panels, Engineered Wall Panels, Vinyl/Fiberglass/Wood Windows, Unprimed Concrete

Surface preparation: Free from dust, debris, and protrusions

Application: Hand applicator or roller should always be used to apply HydroFlash™ for optimal adhesion

Temperature Requirement: Can be installed from 0°F - 180°F

UV Rated: Maximum 180 days

See www.benjaminobdyke.com for complete warranty guidelines, installation instructions, drawings, test reports, and technical bulletins