

# HYDROFLASH®

## Self-Adhered Flashing

HydroFlash® Self-Adhered Flashing is specially formulated for aggressive adhesion to Benjamin Obdyke housewraps. It is compatible with a wide array of sealants and does not contain VOCs, HFCCs, or CFCs. HydroFlash can be installed in cold temperatures and features a split-release liner for quick installation. Taping of Benjamin Obdyke housewrap seams is not required, but if you must tape, use HydroFlash 2.5 inch sealing tape.



### HYDROFLASH®

SELF-ADHERED FLASHING

<b>Width</b>	2.5 in, 4 in*, 6 in*, 9 in or 12 in (6.4 cm, 10.2 cm, 15.2 cm, 22.9 cm, 30.5 cm)
<b>Length per roll</b>	75 ft (22.85 m)
<b>Adhesive</b>	Synthetic
<b>Max. UV exposure</b>	180 days
<b>Temperature Range</b>	Install down to 0°F, store above 40°F
<b>Warranty</b>	10 (product) or 15, 25 (system) year limited

\*Also available in black for open joint cladding applications (HydroFlash UV)



Specially formulated synthetic adhesive that outperforms butyl and rubberized asphalt flashings


Can be installed down to zero degrees fahrenheit (store above 40 degrees fahrenheit)



Fungicide additive restricts mold growth

AAMA 711 approved, meets criteria of AC 148

Seals around fasteners



Split-release liner

Installs easily in cold and/or damp environments

No primer needed