

HYDROGAP®

Drainable Housewrap


HydroGap® Drainable Housewrap is the best performing drainable housewrap on the market. This product allows construction professionals to Build Better™ by effectively eliminating excess moisture, thereby preventing the damaging effects of mold and rot. Its patent-pending one millimeter spacers allow at least 100x more bulk water to drain from a wall versus standard housewraps and drains water 2x faster than any other drainable housewrap on the market.



Thickness (size of gap)	.04 in (1 mm)
Width	5 ft (1.5 m)
Length per roll	100 ft (30.48 m)
Max. UV exposure	120 days
Warranty	10 (product) or 15 (system)
Composition	Polypropylene tri-laminate
Vapor Permeability	16 perms
Fire Rating	Class A



Provides a True Drainage Gap - 1mm compression resistant spacers assures a continuous and efficient drainage gap



Superior Strength and Water Holdout - tri-laminate substrate with water holdout layer sandwiched by two non-woven layers to protect it from damage during installation



Breathable - 16 vapor permeability rating allows moisture to escape quickly before it damages the sidewall materials

Seam Tape Not Required – saves material, time, and labor costs of taping seams

Omni - Directional Design - can be installed in any direction without affecting performance

15 Year Product and Labor Warranty – guarantees performance (not just manufacturing defects), up to \$20,000 per dwelling

Meets requirements of major siding manufacturers such as James Hardie® and Boral® for applications where drainable housewraps are recommended or required

Recommended for all categories of siding

*When calculating material needs for a project, consider requirements for overlapping the housewrap per installation instructions.

James Hardie® is a registered trademark of James Hardie Building Products, Inc. Boral® is a registered trademark of Boral Limited.