



SLICKER® CLASSIC

Rainscreen

Provides big gap (.25 inch & .40 inch) that allows for drainage and drying in the wall assembly



Provides maximum protection for the wall system, eliminating the deteriorating effects of mold and rot between siding and sheathing



Reduces the chances of premature peeling or blistering of finishes

Prevents damage from surfactants by separating the cladding from the water resistive barrier



Saves time and labor costs by eliminating the need for furring strips

Recommended for wood siding

Slicker® Classic is the original rolled rainscreen. The unique, vertically-channeled, three-dimensional matrix of Slicker provides a continuous space for drainage and drying—eliminating the threat of trapped moisture.



Slicker **CLASSIC** Slicker **10 CLASSIC**

Original rolled screen

Meets Canadian code for rainscreen

	Slicker CLASSIC	Slicker 10 CLASSIC
Thickness (size of gap)	.25 in (6 mm)	.40 in (10 mm)
Width	39.37 in (1 m)	39.37 in (1 m)
Length per roll	46.5 ft (14.17 m)	38.5 ft (11.74 m)
Coverage per roll	150 ft ² (13.94 m ²)	125 ft ² (11.61 m ²)
Max. UV exposure	30 days	
Warranty	20 (product) or 25 (system)	
Composition	Nylon (10% pre-consumer recycled)	
Vapor Permeability	Not applicable	

Recommended accessories:

FLATWRAP^{UV}
HYDROFLASH[®]
HYDROCORNER
SLICKER
 SCREEN