


SLICKER® MAX

Rainscreen

Slicker® MAX rainscreen includes a filter fabric, providing enhanced UV and compression resistance. Slicker MAX is ideal for providing drainage and ventilation behind fiber cement, stone veneer and stucco applications.




Provides big gap (.25 inch & .40 inch) that allows for drainage and drying in the wall assembly

Fabric serves as “sacrificial layer” in stone or stucco applications, while preventing mortar from blocking drainage and drying capacity



Additional fabric layer protects matrix from UV exposure and adds compression resistance

Provides maximum protection for the wall system, eliminating the deteriorating effects of mold and rot between siding and sheathing



Reduces the chances of premature peeling, blistering, or cracking of finishes

Prevents damage from surfactants by separating the cladding from the water resistive barrier

Recommended for stone veneer, stucco, and fiber cement siding

Recommended accessories:

FLATWRAP^{UV}

HYDROFLASH

HYDROCORNER

**SLICKER
SCREEN**



Slicker MAX

Rainscreen with maximum UV + compression resistance

Slicker 10 MAX

Meets Canadian code for rainscreen

Thickness (size of gap)	.25 in (6 mm)	.40 in (10 mm)
Width	39.37 in (1 m)	39.37 in (1 m)
Length per roll	61.5 ft (18.75 m)	38.5 ft (11.74)
Coverage per roll	200 ft ² (18.58 m ²)	125 ft ² (11.61 m ²)
Max. UV exposure	90 days	
Warranty	20 (product) or 25 (system)	
Composition	Polypropylene (40% pre-consumer recycled)	
Vapor Permeability	Not applicable	