

# FLATWRAP® HP

COMMERCIAL-GRADE WRB

FlatWrap® HP is a commercial-grade water resistive barrier (housewrap) with enhanced tear resistance. FlatWrap HP is a perfect complement to Slicker® products as the WRB component in a rainscreen wall system.

Tri-laminate design resists damage from surfactants that can compromise other brands of housewrap

Taping of seams is not required, reducing both labor and material costs

To achieve 15 year product and labor warranty, pair with any of Obdyke's flashing options

HORIZONTAL SEAMS: MIN. 4 INCH  
VERTICAL SEAMS: MIN. 6 INCH  
CORNERS: MIN. 12 INCH OVER

|                    |                                        |
|--------------------|----------------------------------------|
| Width              | 3 ft (1 m), 5 ft (1.5 m), 9 ft (2.7 m) |
| Length per Roll    | 100 ft (30.48 m)                       |
| Max. UV Exposure   | 120 days                               |
| Composition        | Polypropylene Tri-Laminate             |
| Vapor Permeability | 15-20 perms*                           |
| Fire Rating        | Class A                                |
| Warranty           | 10 (product) or 15 (system)            |

\*Pending final AC38 test results

**BENJAMIN  
OBDYKE**

roof & wall products

800.523.5261 • [info@obdyke.com](mailto:info@obdyke.com)