

UV-PROTECTED RAINSCREEN INSTALLATION INSTRUCTIONS

invisiwrap® uv

hydroflash® uv+

batten uv

25 YEAR SYSTEM WARRANTY REQUIREMENTS

APPROVED COMPATIBLE PRODUCTS

SELF-ADHERED FLASHING

Benjamin Obdyke® HydroFlash® UV+
SIGA™ Wigluv Black

BATTENS/FURRING STRIPS

Benjamin Obdyke® Batten UV
Wood Furring Strips

CAULKS AND SEALANTS

HydroFlash® LA
OSI® QUAD® MAX Sealant
Loctite® Premium® Construction Adhesive
Loctite® PL Premium® S40 Polyurethane
GeoCel® 2300 Construction Tripolymer
GeoCel® Pro Flex®
Fortifiber® Moistop® Sealant
Bostik® 915™ Polyurethane Sealant
Bostik® 915FS™ Polyurethane Sealant
Dow Corning® 732 Multi-Purpose Sealant
NPC® Solar Seal #900
Titebond® Heavy Duty Construction Adhesive
Titebond® WeatherMaster™
Titebond® WeatherMaster™ ULTIMATE MP
Tremco® Vulkem® 116
DAP® Flexible Clear Sealant

VIRTUAL JOBSITE VISIT

Project specific installation training and window mockups are recommended to verify proper details and reduce the learning curve for installers and design professionals.

To ensure you're achieving the maximum warranty, please contact us at techsupport@obdyke.com, or fill out the request form on our website,

OR SCAN THE QR CODE HERE.

