

# VAPOR DRY™ SA

VAPOR PERMEABLE SELF-ADHERED ROOF UNDERLAYMENT

A unique self-adhered roofing membrane with vapor permeability, reducing potential of damage due to moisture build-up

Continuous acrylic adhesive is repositionable during install and self-seals around roofing fasteners

Can be used with Cedar Breather Ventilated Underlayment for maximum drying potential in wood, metal, and cold roof applications

Approved for use with all roofing types with a pitch 3:12 or greater

Provides enhanced protection from the elements during 'dry-in' period

Slip-resistant surface & printed overlap guides for an easier install

Meets ASTM D1970 testing standard for roofing underlayment

High temperature self-adhered underlayment: 250°F service temp.



<b>WIDTH</b>	4.75 ft (1.45 m)
<b>LENGTH PER ROLL</b>	80 ft (24.38 m)
<b>MAX. UV EXPOSURE</b>	120 days
<b>COMPOSITION</b>	Polypropylene Tri-Laminate
<b>VAPOR PERMEABILITY</b>	14 perms ASTM E96(a)
<b>ADHESION</b>	Continuous Acrylic
<b>GROSS COVERAGE</b>	380 sq. ft./roll
<b>ASTM AC38</b>	pass
<b>SERVICE TEMPERATURE</b>	250°F